

MIRROR IMAGE
Teleprompters, Inc
MIRROB IMAGE
20 Years serving YOU!



America's Leading Innovator of Cost Effective Prompter Designs



Introducing the new **OUTDOOR**
Speechprompter...**SP-160HB**

*Dual 15" LCD Day-Bright monitors
with multiple inputs and
Metal LCD cabinet

*Includes distribution-amp

*12.75"x10" Beamsplitter Mirrors
12.75"x10" Tinted Mirrors
12.75"x10" True Mirrors

*Mirrors are vertically adjustable and
can be tilted for any individual needs

*Monitors are placed on the floor and
are protected by metal housing

*Housings "nest together" for
easy portability

*All metal components with
a durable powder coat finish.
Extremely tough!

*3 year conditional warranty.
It doesn't get better than that!

*Generally in stock & ready to ship.

*250 Dealers worldwide are ready
to serve you!



Specifications	SP-160HB
Viewable Size	15 inch
Brightness	1800 NTS
Signal Input	SVGA, NTSC S-Video
Video Input Impedance	1 VOLTS P-TO-P
Input Voltage	100-240 VAC 12 Volt DC
Resolution	1280x1024
Power Consumption	70 Watts
Input Connector	15-pin D-Type BNC, 4-Pin
Special Features	Scan-Reverse BNC Loop

USD.14.500,

MIRROR IMAGE
Teleprompters, Inc
MIRROR IMAGE
20 Years serving YOU!



America's Leading Innovator of Cost Effective Prompter Designs



**Introducing our best selling podium
Speechprompter...SP-160**

*Dual 15" LCD monitors
with multiple inputs and
Metal LCD cabinet

*Includes distribution-amp

*12.75"x10" Beamsplitter Mirrors

*Mirrors are vertically adjustable and
can be tilted for any individual needs

*Monitors are placed on the floor and
are protected by metal housing

*Housings "nest together" for
easy portability

*All metal components with
a durable powder coat finish.

Extremely tough!

*3 year conditional warranty.
It doesn't get better than that!

*Generally in stock & ready to ship.

*250 Dealers worldwide are ready
to serve you!



Specifications	SP-160
Viewable Size	15 inch
Brightness	450 NTS
Signal Input	SVGA, NTSC S-Video
Video Input Impedance	1 VOLTS P-TO-P
Input Voltage	100-240 VAC 12 Volt DC
Resolution	1280x1024
Power Consumption	30-35 Watts
Input Connector	15-pin D-Type BNC, 4-Pin
Special Features	Scan-Reverse BNC Loop

